

## INTRODUCTION

**Congratulations on purchasing the Fast Find Personal Location Beacon (PLB). When carrying a Fast Find you enjoy the reassurance of a last resort safeguard against any life threatening incidents that may occur anywhere in the world. If you find yourself in a remote area without any other form of emergency communication, on land or at sea, your Fast Find can call for help.**

Fast Find will transmit a unique emergency identifier to the Cospas Sarsat satellite system which can determine your location anywhere on the earth's surface. In most cases the emergency alert is received within 5 minutes of activation but depending on satellite coverage at the time this can sometimes extend to 45 minutes.

When the emergency alert message is received at a Rescue Co-ordination Centre (RCC) it is cross referenced using the unique identifier (often called Hex ID) against your registration details. Detail of the alert is forwarded to the appropriate local Search And Rescue (SAR) teams. Keeping your registration details up to date is critical to ensuring a quick SAR response.

Fast Find has a secondary 'homing' transmitter which allows SAR teams to direction find or 'home' on it once they arrive on scene. Fast Find has a storage life of 5 years and once activated will continue to transmit emergency alerts for a minimum of 24 hours.

For further information visit Cospas Sarsat on line at [www.cospas-sarsat.org](http://www.cospas-sarsat.org) and [www.mcmurdo.co.uk](http://www.mcmurdo.co.uk). The 'frequently asked questions' section is a good place to start.

## OVERVIEW

- Red pull handle**  
Pull to expose antenna  
**Only pull in an emergency**  
Pulling breaks the plastic anti-tamper seal that can not be reset by the user.
- White indicator Light**  
Flashes every 3 seconds once PLB is active, Long flash every 50 seconds means satellite transmission OK  
*For PLB 210 only*  
Flashes twice a second when GPS is searching  
3 rapid flashes means GPS location sent
- Antenna**  
Unwraps and stands vertical once cover is off
- GPS antenna zone**  
(PLB 210 only)  
*Do not obstruct*  
Needs a clear view of the sky for best operation
- ON button**  
Press once to activate PLB.  
When the PLB is on, push the ON button again to make the indicator light flash an SOS signal pattern.
- TEST / OFF button**  
Push and hold to start the self test feature, a flash of white light indicates that the self test is successful.  
*Once PLB is active*  
Hold TEST to turn PLB off
- Eyelet for lanyard**



## ACTIVATING THE FASTFIND PLB

Only ever activate in situations of grave or imminent danger.

- 1) Flip up the red pull handle, Pull the antenna cover off**  
**IMPORTANT**

The antenna cover is an anti-tamper seal, once broken it can not be refitted.



- 2) Hold the end of the antenna, Unwrap the antenna until it stands vertical**

## CAUTION

Spring action antenna deployment; tilt the PLB away from your face before deploying the antenna.



- 3) Press the ON button**

Transmission of the first emergency alert message takes place 50 seconds after initial activation, in the event of an accidental or false activation this delay allows time for the user to turn off the Fast Find before the first alert is transmitted.



## DEPLOYING THE PLB

- Always position the PLB so that the antenna stands vertical
- If it's windy, rotate the PLB so that the white indicator light faces into the wind



Do NOT allow the PLB to tip over



Do NOT hold the antenna



Do NOT allow the antenna to sit in a puddle of water

Do NOT cover the GPS antenna zone

## Use around water

The Fast Find will NOT float but is waterproof to 10 meters submersion for short periods. To avoid loss if dropped into water fit a retaining lanyard through the eye hole in the base of the PLB and fasten it securely to your clothing or personal flotation device.

The PLB is not a substitute for an EPIRB that may be required under maritime regulation.


Note: In some countries the Fast Find PLB may be sold with an auxiliary flotation device but is not designed to float in an upright position or transmit a distress alert when floating in water.



## INDICATOR LIGHT

The indicator light will start flashing immediately the Fast Find is activated

## FAST FIND 200 Light indication



PLB ACTIVE  
1 flash every 3 seconds



SATELLITE TRANSMISSION OK  
Large flash once every 50 seconds

## FAST FIND 210 WITH GPS Light indication



GPS SEARCHING  
2 flashes every 1 second



SATELLITE TRANSMISSION SENT WITH  
GPS LOCATION OK  
Sequence repeats every 50 seconds



PLB ACTIVE  
1 flash every 3 seconds

## FLASH SOS FEATURE

When the PLB is active, pressing the ON button will cause the indicator light to flash a Morse code SOS pattern. This can be used to attract attention after nightfall. The SOS pattern is repeated four times on each press.



To conserve battery life a maximum of 30 presses are allowed, after which this feature is disabled.



## DE-ACTIVATION AFTER USE

To turn off the Fast Find, press and hold the TEST button for several seconds until the indicator light stops flashing.

We recommend the antenna is re-wound under the plastic peg. If possible, the yellow antenna cover should be pushed back in place and temporarily taped over, to avoid accidentally pressing of the ON button.



## Important

As soon as possible the PLB should be returned to a service agent, who will fit a new antenna cover and check the battery condition. If the PLB was active for more than a few hours we recommend fitting a fresh battery to ensure the full 24 hour operational life is still available.

## SELF TEST

Self-test verifies operation of the PLB by checking all key features including the battery and alert transmitters.

## TEST button

Push and hold the SELF TEST button for a minimum of 2 seconds, the



indicator light will flash once to indicate the start of the self test sequence.

After a few seconds, a good self-test will result in the indicator light flashing a number of times in quick succession depending on battery usage;

fresh battery self test pass

minimum usage self test pass

medium usage self test pass

**NO FLASH** self test fail PLB requires service

The PLB will switch off automatically when the self-test has completed.

## Important

Each self-test draws small amounts of energy from the battery pack. Unnecessary testing of the PLB will reduce the run time of the PLB in an emergency. On average, the PLB should only be self tested 12 times per year, or a total of 60 times during the 5 year battery lifetime.

**GPS POSITION ACQUISITION TEST**

When testing the GPS, take the PLB outside into an open space with a clear view of the surrounding sky.

Self testing of the in-built GPS is restricted to a maximum of 10 tests throughout the 5 year storage life of the battery. Once all the tests have been used up, attempting further tests will cause the indicator light to flash 4 times in quick succession and the PLB to power off.

The GPS self-test feature can only be accessed after first completing a standard PLB self-test routine;

Push and hold the TEST button for a minimum of 2 seconds, the indicator light will flash once to indicate the start of the self test sequence. Release the TEST button.

After a few seconds the standard self-test routine will complete and should result in the indicator light flashing a number of times in quick succession depending on the past battery usage.

Immediately after the indicator light stops flashing, hold down the TEST button for around 30 seconds. The GPS test routine starts when the indicator light begins to flash, now release the TEST button. The light will continue to flash slowly for up to 5 minutes; you should continue to watch the PLB throughout this period.

A successful GPS test is signalled by the indicator light flashing a number of longer flashes in quick succession.

**Important**

To preserve battery life, GPS testing is restricted to a maximum of 10 tests throughout the 5 year battery life. Once used up, further GPS tests are prohibited.

**CHOOSING THE BEST LOCATION**

The *Fast Find* works best under an unobstructed view of the sky. This ensures the emergency alert message reaches the satellite system and gives the GPS receiver (*Fast Find* 210) the best signals to work with.

**If it's not possible to pick a location with an unobstructed view of the sky, then try to maximize the amount of sky available.**

Tree canopy degrades performance. Find a clearing with as much sky view as possible. Ravines, canyons, caves and overhangs should be avoided if at all possible.

**Stay put** - Rescue teams expect you to remain stationary. Trying to walk for help is generally not advised and will probably slow down the rescue effort.

**On foot**

If you must walk for help, ensure the *Fast Find* antenna remains vertical.

**Aircraft**

A PLB is often used as an additional carry-off safety device. The PLB should NOT be activated aboard an aircraft. The signal will be blocked by metalwork and the PLB may be damaged by any impact. Activate the PLB after landing, away from the aircraft, as it may cause shadowing.

**Vehicles**

The PLB will not work well inside a vehicle due to metalwork shadowing. Exit the vehicle, activate the PLB, and place it on the roof, the hood, or just on the ground away from the vehicle.

**Land**

Find the best sky view, then place the PLB on flat ground. Keep the antenna pointing towards the sky and ensure wind doesn't knock the PLB over. Do NOT allow the antenna to sit in a puddle of water.

**Aboard ship**

Place the PLB flat on the deck, choosing a position with the best sky view.

**Liferaft**

Try to keep the PLB flat and try to elevate the PLB to avoid bodies blocking the signal. Consider holding the PLB outside the canopy. But first attach a lanyard between the PLB and your clothing to avoid loss of the PLB.

**Lifejacket**

Attach a lanyard cord between the PLB and clothing to avoid loss of the PLB. Hold the PLB flat on top of the life vest and try to keep it above any wave wash. Keep the antenna vertical. Avoid holding the antenna, or blocking the GPS zone with your hand.

**False alerts**

If the PLB has been accidentally activated, or if rescue has been effected before arrival of the rescue services:

- Switch off the PLB and notify the appropriate rescue services or authorities at the earliest possible time.
- Contact the rescue services, coastguard, or police by radio or telephone to advise them of the false alert.

In the U.S. call 1-800-851-3051

In the UK call MRCC Falmouth +44 (0)1326 317575

**TRANSPORTATION****Passenger Aircraft;**

These products contain small lithium metal batteries. They can normally be carried on board passenger aircraft as a personal item in carry-on baggage. McMurdo always recommends declaring the PLB to airline staff at check in, in the same way you would for a laptop PC or video camera.

**As air cargo;**

These products contain small lithium metal batteries. Due to the overall low level of lithium content they are not restricted as air cargo under IATA SP 188 - PI 970, always check with the carrier concerned for any additional restrictions that could apply.

**END OF LIFE STATEMENT**

At the end of the products useful life, it is vital that the battery is removed from the main body of the PLB to prevent false alerts. False alerts cause expensive disruption to Search and Rescue services and may endanger lives as a consequence.

**Safe disposal**

Contains traces of lithium, may contain lead and brominated flame retardants (BFRs), both in the housing material and circuit boards.

**DO NOT INCINERATE**

McMurdo strongly recommends that this PLB product is disposed of in a sensible and considerate manner. For example, do not simply discard the product in the domestic waste. Instead take it to a civil recycling facility, or contact McMurdo for advice.

**FAST FIND 200, 210**

<b>STANDARDS APPLIED</b>	COSPAS-SARSAT T,001/T,007 class2 RTCM SC110 STD 11010,2 ETSI EN 302-152-1 AS/NZS 4280.2 NSS-PLB06	<b>ELECTRICAL</b>	406,037 MHz transmitter ± 1KHz, 5W ± 2dB 121.5 MHz transmitter ± 3KHz, 50mW ± 3dB PERP Homer sweep direction UP or DOWN Transmit Antenna Deployable flexible vertical blade Programming interface Optical Infra-red link
<b>ENVIRONMENTAL</b>	Exterior Finish Highly visible yellow Sealing Waterproof to 10m (30ft) (IP 58, IPX8) Operating temperature Class 2, -20°C to +55°C (-4°F to +131°F) Storage Temperature Class 2, -30°C to +70°C (-22°F to +158°F) Altitude 40,000 feet	<b>PHYSICAL</b>	<i>Fast Find</i> 200, 210 Category 2, will not float Size (D x W x L) 34 x 47 x 106 mm (1.34" x 1.85" x 4.17") Weight 150g ( 5.3 oz) GPS ( <i>Fast Find</i> 210 only ) 50 channel Receive Antenna Ceramic Patch GPS Self test Position acquisition test (10 operations allowed)
<b>BATTERY</b>	Battery Type 6V Lithium Metal Battery storage 5 years Battery replacement By service centre Battery use Logged by microcontroller	<b>PART NUMBER</b>	91-001-200A <i>Fast Find</i> 200 PLB retail pack 91-001-210A <i>Fast Find</i> 210 PLB (with GPS) retail pack
<b>OPERATION</b>	Activation Three stage manual activation Self test Tests transmitters, battery and light SOS flash light Morse code SOS pattern (30 operations allowed)	<i>FAST FIND 200, 210 models do not float and are not recommended for use on or in water unless provided with an auxiliary flotation device. A Fast Find PLB is not an ELT or an EPIRB and does not meet the regulatory requirements for an ELT or an EPIRB.</i>	
<b>TRANSPORTATION</b>	Air cargo UN 3091, not restricted, IATA SP 188 - PI 970		